



 **WOODlife**

douglas 2011



DISCLAIMER

WOODlife Flooring is a trade name of NEDlit International UAB. WOODlife Flooring is registered by the Chamber of Commerce under nr. 1114 75323. WOODlife Flooring cannot guarantee the accuracy or completeness of the information provided in this brochure. The information provided is purely of an indicative nature and is subject to change without notice at any time. WOODlife Flooring does not accept any liability for the content of this brochure. The information and content in this brochure may not be copied, transferred, duplicated, processed or distributed. All copyrights, including those within the meaning of Section 15 of the Copyright Act, are reserved.

© 2010 **WOODlife Flooring**

Cover pictures: © Dinesen

Xtra wide and Xtra long solid Douglas 2011

Douglas originates from the regions of the west coast of North-America en was introduced in the Netherlands around 1850. Nowadays Douglas covers appr. 7-8% of the Dutch forest area. The timber of the Douglas which originates from North-America is sold in Europe under the name of Oregon pine. Timber of Douglas that is grown in Europe is sold under the name 'Douglas'. The colour of the core of Douglas is light reddish to brown-red. Douglas is, even as larch, one of the most durable coniferous wood species from European forests. After drying, the timber becomes very hard. When nailing or screwing the timber, it is recommended to pre-drill the timber in order to prevent the timber from splitting. *NB Douglas contains resin, which can sometimes come up even after a few years.*

Thickness	Width	Length	Nature	Robust
28 mm	260 mm	4000-6000 mm	✓	✓
28 mm	260 mm	10000-12000 mm	X	✓
28 mm	300 mm	4000-6000 mm	✓	✓
28 mm	300 mm	10000-12000 mm	X	✓



Specifications

- Specie: douglas (Pseudotsuga menziesii)
- Moisture content: KD 8-10%
- Tongued and grooved lengthwise, the head ends are not processed (and have to be square cut during the installation of the floor)
- Microbevel alongside or square edge
- Kerfs on the back of the boards
- Grading: Nature or Robust
 - Nature: sound knots up to 2 cm, no fallen out knots, little sapwood in max 15% of the boards, minor cracks because of drying are filled.
 - Robust: sound knots up to 5 cm, no fallen out knots, open defects filled, sapwood allowed, heart allowed up to max 2 meter, end cracks up to 10 cm allowed, minor cracks because of drying are filled.
- Packing: packed in cling film on pallets

Terms of delivery

- Incoterms & prices: EXW Netherlands, Incoterms 2000.
- Transport can be organised by Nedlit International.
- Delivery time: appr. 8-10 weeks.
- Our General Sales and Delivery Conditions apply to all our sales.